

JKV-8PS2R



8-port 19" Rackmount KVM Switch w/ Front-panel Buttons and Keyboard Hotkey Control

This JKV-8PS2R Rackmount PS/2 KVM Switch is designed for computer/server management on a centralized single admin desk in corporate, factory as well as in campus computing environment. It also features a hot-plugging capability that allows you to plug off and on the KVM cabling without powering down a whole rack of servers, especially convenient when you are working on a server rack.

ROBUST AND RELIABLE FOR CORPORATE SERVER ROOM / INDUSTRIAL FLOOR

The JKV-8PS2R Rackmount PS/2 KVM Switch is robust and durable in metal enclosure and provides better shielding against electromagnetic interference commonly seen in lab or factory environments. The metal case offers a sturdy protection needed to withstand accidental impact.

CENTRALIZED RACKMOUNT MANAGEMENT

The JKV-8PS2R features a console port to connect your shared keyboard, video and mouse, and 8 PC ports to connect to your computers/servers. The rackmount design offers a neat placement of the KVM Switch units on the rack for centralized management and also for security enhancement that could be provided by a locked server room. You can simply place it on desktop or mount it on a standard 19" rack for more secured and centralized management.

Features

- 8-port 19" Rackmount PS/2 KVM Switch in metal enclosure
- PS/2 style keyboard and mouse control
- Support Microsoft IntelliMouseR, IntelliMouse ExplorerR, Logitech NetMouseR and other compatibles
- Direct channel selection and operation using Front-panel push buttons and keyboard hotkeys
- Support for DOS, Windows 95/98/SE/ME/2000/XP, Linux, etc.
- Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs
- Mouse reset hotkey for non-PnP OS such as Win NT 4.0 and Linux
- LED indicators for easy port status monitoring
- Plug-and-play, no Windows driver software needed for PS/2 keyboard and PS/2 operation
- Buzzer sound for port switching confirmation
- Autoscan mode for quick browsing of all connected computers
- Autoscan delay time programmable 5 ~ 100 seconds through hotkey commands
- High VGA resolution 1920 x 1440
- 19" rack mount design with metal enclosure for best shielding and protection



Specifications

MODEL	JKV-8PS2R
PC Connections	• 8
Console Connections	• 1
PC Port Connectors	• 8 x PS/2 Keyboard 6-pin Mini Din female • 8 x PS/2 Mouse 6-pin Mini Din female • 8 x VGA HDB 15-pin female
Console Port Connectors	• 1 x PS/2 Keyboard 6-pin Mini Din female • 1 x PS/2 Mouse 6-pin Mini Din female • 1 x VGA HDB 15-pin female
PC selection	• Hotkeys / Push buttons
On Screen Display	• No
PC port LED	• 16
Scan delay time	• 5~100 sec. programmable through hotkey
Keyboard/Mouse emulation	• PS/2
VGA Resolution	• 1920 x 1440
Power Type	• PS/2 interface power
Power Adapter	• (Optional) DC 9V 1A
Operation Temperature	• 0 ~ 40 °C
Storage Temperature	• - 20 ~ 60 °C
Humidity	• 0~90% RH, non-condensing
Size	• Standard 19" rack mount
Housing	• Metal enclosure
Dimension (L x W x H)	• 410x 165 x 44.5 mm
Weight	• 2200g
Safety / Emission	• FCC, CE

Ordering information

Model	Description
JKV-8PS2R	8-port Rackmount PS/2 KVM Switch (metal case)

