

JSH4726GBM



Layer-3 Fast Ethernet plus 4 Giga port (support auto copper/fiber) switch

The switch is an L3 24-port Fast Ethernet switch plus 4 Gigabits port(support auto copper/fiber switching),with high performance and competitive price. It's a perfect way to extend your network structure.

KEY FEATURE

- Compliant with the IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX ,IEEE802.3ab 1000Base-T ,IEEE802.3z 1000Base-X specifications
- 24 port 10/100Mbps TX Auto-Negotiation and 4 port 10/100/1000Mbps TX and 2 1000Mbps SFP port(shared with 10/100/1000M port)
- Supports TP interface Auto MDIX function for auto TX/RX swap
- Support up to 16K MAC address,16K IPv4 routing table
- Up to 256M bits packet buffer
- Supports Store & Forward architecture and performs forwarding and filtering
- Supports Jumbo frame up to 9KB
- Support RIP1/RIP2 routing
- Supports port-based , VLAN 802.1q tag VLAN(up to 4K group)
- Supports rate control(64Kbps-80Mbps)
- Supports port mirror
- Supports IEEE802.1D Spanning Tree and IEEE802.1w RSTP protocol
- Supports SNMP V1/V2 ,RMON MIB(group 1,2,3,9)
- Supports access switch through Web/Telnet/Console
- Supports firmware upgrade through Web/Console
- Build-in power

SPECIFICATIONS

Chip: BCM5650+BCM5248+BCM5464S+IXP420

Standards: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX,IEEE802.3ab 1000Base-T ,IEEE802.3z 1000Base-X

Access Method: CSMA/CD

Network Media: UTP CAT3 or up for copper port ,Single-mode or Multi-mode fiber(with SFP connect) for fiber port

Transmission Method: Store and Forward

MAC Address Table: 16K

Built-in Buffer: 256M bits

Data Transfer Rate: 10/100Mbps (Half-duplex), 20/200/2000Mbps (Full-duplex for copper port),2000Mbps only for fiber port

LED Indicators: Power, Link/Activity

Dimension: 438mm(L) x 250mm(W) x 44mm(H)

Weight: 5000g

Temperature: 0° to 50° C (operating), -20° to 70° C (storage)

Humidity: 5% to 90 % non-condensing (operating), 5% to 90% non-condensing (storage)

Certifications: FCC Part 15 Class A, CE Mark



ORDERING INFORMATION

MODEL	Description
JSH4726M	Layer-3 24 Port Fast Ethernet Switch plus 4 giga port switch (Support auto copper/fiber switching)

