



JLP2200 is a full-featured IP-based telephone set for home telephony via Ethernet base communication. It supports SIP RFC3261 protocol. Two 10/100BaseT embedded switch/hub RJ-45 ports allow connect to office LAN and PC on your table. It is easily interface with ADSL/Cable Modem that is provided by ITSP, ISP or Carrier company to provide VoIP services to residential and SOHO application.

FEATURES

- **Built-in two 10/100BaseT Switch**

The internal two-port Ethernet switch allows for a direct connection to a 10/100BaseT Ethernet network via an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. The system administrator can designate separate virtual LANs (VLANs) (802.1P1Q) for the PC and Welltech IP Phones.

- **Big Key**

Those Keys are big in the phone-set JLP2200. It is easy to use for old man and children at home.

- **Big LCD screen**

The LCD of JLP2200 shows big characters that easy to reading for old man and children at home.

- **Graphic Memory key**

There are five memory keys in the left side of JLP2200 that will show by different graphic pictures. It is very easy to understand and operation by old man and children at home.

- **Easy to installation**

Users can set up the phone-set JLP2200 by themselves through easy installation guide and steps of LCD panel.

- **High cost-effective phone-set**

SPECIFICATIONS

MODEL	JLP2200
WAN interface	• One RJ-45 10/100 BaseT
LAN interface	• One RJ-45 10/100 BaseT
Power Adapter	• 5V DC
LCD Display	• 13 character , 2 lines
Function Key	• 4
Memory Key	• 5
Menu control Key	• 4
Hand free Speaker phone	• With Echo cancellation
Network Connect	• Fix IP, DHCP, PPPoE
Link Mode (SIP)	• Proxy mode and Peer to peer mode
Link Mode (H323)	• Peer to Peer, Gatekeeper mode, DDNS mode
Protocol	• SIP (RFC3216)
Audio Codec support	• G.711U, G.711A, G.723.1, G.729, G.729A
QoS Support	• VLAN (802.1p/q)
Telephony features	• Mute, Forward, Hold, Redial, Transfer
Configure management	• LCD Front Panel, Web Browser, Telnet, Welltech's EMS
DTMF (SIP)	• In-band, RFC 2833 out-band DTMF generation/detection
Certification	• CE ,FCC
Humidity	• (10 to 90%) non-condensing, operating, and non-operating/storage
Operational Temperature	• (0 to 40°C)
Storage Temperature	• (-10 to 60°C)
Dimension	• 200mm(W) x 79mm(H) x 210mm(D)
Weight	• 830 g

ORDERING INFORMATION

Model	Description
JLP2200	An IP Phone solution provides telephone call over an IP-Network